



PRIMO

LED STRIP STR-PRIMO





Primo features 240mm divisible length segments, allowing you to customise the ideal length for your cove lighting project. Primo features on-board dimming and thermal management.


Primo is designed for concealed cove lighting applications where value and ease of installation is paramount.

POWER


LUMINOUS FLUX

10W

10.8W / metre



SD • 800 lm / metre



RD • 670 lm / metre



P17D • 570 lm / metre

COLOUR TEMPERATURE

2700K

3000K

4000K

5000K

HIGH PERFORMANCE

ECONOMICAL

Primo is designed to provide the highest lumen output for budget applications. It offers a reasonably high lumen package while maintaining high performance and exceptional reliability.

VERSATILE LENGTH OPTIONS

Versatile length options allow the user to achieve accurate and adaptable lengths. Primo can achieve any desired length in 240mm increments.



LONG OPERATING LIFE

Coolon products use the world's most reputable LED manufacturers and the latest available standards to adequately report lumen maintenance. We strive to drive LEDs under their nominal current and use state-of-the-art heat dissipation methods, leading to durable electronics.



VARIOUS CCT & COLOUR BINNING CONSISTENCY

All products are offered in various colour temperatures, and manufactured using tighter bins, ensuring excellent consistency and uniformity.



5 YEARS WARRANTY

Coolon luminaires are covered by a solid comprehensive manufacturer's warranty that covers a range of possible defects and performance parameters throughout the duration of the warranty period.




PROUDLY MADE IN AUSTRALIA

Our products are designed and manufactured in Australia. Engineered to perfection, using only the highest quality components and highly skilled labour, each luminaire is assembled and thoroughly tested to ensure that it exceeds the highest standards.

TECHNICAL SPECIFICATIONS


Product Code	STR-PRIMO
Description	Primo High Power LED Strip
Segment Length (S)	480mm
Sub-Segment Length (A)	240mm
Number of Sub-Segments	2
Segment Width	10.50mm
LED Pitch	40.00mm
LEDs Per Segment	12
LEDs Per Sub Segment	6
Operating Voltage	24VDC
Typical Power Consumption per Segment	5.2W per 480mm Segment
Typical Power Consumption per Metre	10.8W per metre
Typical Current	216mA per 480mm Segment
Colour Rendering Index (CRI)	80+
Dimmable	Through CTR-DALILOGIC or CTR-DIMMERLOGIC (sold separately)
Effective Beam Angle	110°
External Heatsink Required	No
Ambient Operating Temp	Ta -10°C to 50°C
Thermal Operating	Yes (Active)
Average Lumen Maintenance @Ta 25°C	70% @ 50,000 Hours
IP Rating	IP40
Max Continuous Connection Length	Please refer to installation limitations

COLOUR BINNING




DIMENSIONS

For final strip lengths please refer to the "Product Length" table.



STANDARD PROFILE



AVAILABLE IN


Diffused



MOUNTING OPTIONS

- **MC-STR-1513**
Stainless Steel Mounting Clips

REINFORCED PROFILE



AVAILABLE IN


Diffused



MOUNTING OPTIONS

- **MC-STR-RD**
Stainless Steel Mounting Clips

P17 PROFILE



AVAILABLE IN


Diffused



MOUNTING OPTIONS

- **MC-XCLIP**
Flat Mount X-Clip
- **MC-STR-RBCLIP**
Rebate Mounting Clip
- **MC-STR-SMCLIP**
Pivot Surface Mounting Clip
- **MC-P17R**
Rotating Clip Mount

PR17 RECESSED PROFILE



AVAILABLE IN

Diffused



MOUNTING OPTIONS

- **MC-XCLIP**
Flat Mount X-Clip
- **MC-STR-SMCLIP**
Pivot Surface Mounting Clip
- **MC-STR-PR1732**
Spring Mounting Clip



Click on the download icon to view more information regarding mounting and rebate suggestions.

PRODUCT LENGTH WITH SD/RD/P17D

FULL SEGMENTS	SUB SEGMENTS	EXACT STRIP LENGTH	END CAP ALLOWANCE	FINAL LENGTH
S0	A1	240mm	add 25mm	265mm
S1	A0	480mm	add 25mm	505mm
S1	A1	720mm	add 25mm	745mm
S2	A0	960mm	add 25mm	985mm
S2	A1	1,200mm	add 25mm	1,225mm
S3	A0	1,440mm	add 25mm	1,465mm
S3	A1	1,680mm	add 25mm	1,705mm
S4	A0	1,920mm	add 25mm	1,945mm
S4	A1	2,160mm	add 25mm	2,185mm
S5	A0	2,400mm	add 25mm	2,425mm
S5	A1	2,640mm	add 25mm	2,665mm
S6	A0	2,880mm	add 25mm	2,905mm
S6	A1	3,120mm	add 25mm	3,145mm
S7	A0	3,360mm	add 25mm	3,385mm

Confirm interstate courier compliance

PRODUCT LENGTH WITH PR17


FULL SEGMENTS	SUB SEGMENTS	EXACT STRIP LENGTH	END CAP ALLOWANCE	FINAL LENGTH
RS0	A1	240mm	add 40mm	280mm
RS1	A0	480mm	add 40mm	520mm
RS1	A1	720mm	add 40mm	760mm
RS2	A0	960mm	add 40mm	1,000mm
RS2	A1	1,200mm	add 40mm	1,240mm
RS3	A0	1,440mm	add 40mm	1,480mm
RS3	A1	1,680mm	add 40mm	1,720mm
RS4	A0	1,920mm	add 40mm	1,960mm
RS4	A1	2,160mm	add 40mm	2,200mm
RS5	A0	2,400mm	add 40mm	2,440mm
RS5	A1	2,640mm	add 40mm	2,680mm
RS6	A0	2,880mm	add 40mm	2,920mm

Confirm interstate courier compliance

⚠ WARNING

Do not bend LED strip when removing from mounting clips.


Gently twist LED Strip to remove from mounting clips.




⚠ WARNING

PLEASE HANDLE LONG LED STRIPS WITH CARE.

LED Strips must not be bent.



When handling LED Strips, please ensure that they are kept straight.




PROFILE / DIFFUSER

SD - Standard Profile Diffused




RD - Reinforced Profile Diffused



P17D - P17 Profile Diffused



PR17D - PR17 Profile Recessed Diffused



PROFILE COLOUR

Profile colour applicable to P17 and PR17 only.

BLK - Black (Standard)



WHT - White



CST - Custom Colour ¹



¹ Custom colours available on request.

WIRING CONFIGURATION

CONNECTOR TYPE	DRAWING	MALE	FEMALE
WR2.1OS Wire 2+1 Core One Side			
WR2.1BS Wire 2+1 Core Both Sides			
OC2.1MO Outdoor Connector 2+1 pin Male Only			
OC2.1MF Outdoor Connector 2+1 pin Male + Female			
SMPLC.1 Sample Type Connector 2.5mm			

- For detailed information on Outdoor IP67 connector please contact Coolon.
- Please consult Coolon for details on extension cable between LED fittings, drivers and power supplies.




WIRING COLOUR CODE	
Red	+ VDC
Black	GND
White	Dimming

IP RATING

IP40

Protected against solid objects greater than 1mm. No protection against liquids.

■ INSTALLATION LIMITS



MAX. CONTINUOUS CONNECTION LENGTH (X)	CONNECTOR TYPE
12,000 mm	With standard 2+1 core (WR2.1OS / WR2.1BS)
17,000 mm	With upgraded 4+1 core (WR4.1OS / WR4.1BS)
5,400 mm	With upgraded outdoor 2+1 pin connectors (OC2.1MO / OC2.1FO / OC2.1MF)
9,000 mm	With upgraded outdoor 4+1 pin connectors (OC4.1MO / OC4.1FO / OC4.1MF)

• Please consult Coolon for details on extension cable between LED fittings, drivers and power supplies.

⚠ WARNING


Avoid connecting multiple power supplies into a single circuit, unless they are specifically designed to do so.

✗

✗

ORDERING EXAMPLE

STR - PRIMO - 3.0K - S2A1 - P17D - BLK - WR2.1BS - 100 - IP40



COLOUR TEMPERATURE ¹ PAGE 04

2.7K	2700K
3.0K	3000K
4.0K	4000K
5.0K	5000K

PRODUCT LENGTH PAGE 06

FULL SEGMENTS		SUB SEGMENTS
S0	RS0	A0
S1	RS1	A1
S2	RS2	
S3	RS3	
S4	RS4	
S5	RS5	
S6	RS6	
S7		
S8		

PROFILE / DIFFUSER PAGE 07

SD	Standard Profile Diffused
RD	Reinforced Profile Diffused
P17D	P17 Profile Diffused
PR17D	PR17 Recessed Profile Diffused

PROFILE COLOUR ² PAGE 07

BLK	Black (Standard)
WHT	White
CST	Custom Colour

WIRING CONFIGURATION PAGE 08

WR2.1OS	Wire 2+1 Core One Side
WR2.1BS	Wire 2+1 Core Both Sides
OC2.1MO	Outdoor Connector 2+1 pin Male Only
OC2.1MF	Outdoor Connector 2+1 pin Male + Female
SMPLC.1	Sample Type Connector 2.5mm

WIRING LENGTH PAGE 09

100	100mm
250	250mm
500	500mm
1000	1,000mm


IP RATING PAGE 08

IP40	Indoor Use
------	------------

¹ Other CCT subject to availability.


² Profile colour applicable to P17 and PR17 only. Custom colours available on request.

■ ACCESSORIES


	PRODUCT CODE	DESCRIPTION
	MOUNTING CLIP ¹	
	MC-STR-1513	Stainless Steel Mounting Clips for Standard & Low Profile
	MC-STR-RD	Stainless Steel Mounting Clips for Reinforced Profile
	MC-XCLIP	Flat Mount X-Clip
	MC-STR-RBCLIP	Rebate Mounting Clip
	MC-STR-SMCLIP	Pivot Surface Mounting Clip
	MC-P17R-BLK	Rotating Clip Mount for P17 Profile - Black
	MC-P17R-WHT	Rotating Clip Mount for P17 Profile - White
	MC-STR-PR1732	Spring Mounting Clip for PR17 Recessed Profile

¹ Recommended spacing between MC-STR-RD and MC-STR-1513 Mounting Clips is maximum 300mm. Recommended spacing for all other Mounting Clips is maximum 500mm.

CONTROLLER

	CTR-A2PWM 0-10V	Analogue to PWM converter for 0 – 10V dimming signal
	CTR-DIMMERLOGIC	Coolon Universal Wall Dimmer with 0 – 10V and PWM Logic Output
	CTR-DALI-LOGIC	Indoor DALI Point 1 channel Driver with PWM Logic Output
	CTR-DALILOGIC-IP	Outdoor DALI Point 1 channel Driver with PWM Logic Output

POWER SUPPLY

	PWR-HLG-60H-24AU	Mean Well Power Supply HLG 60W 24V IP67
	PWR-HLG-150H-24AU	Mean Well Power Supply HLG 150W 24V IP67
	PWR-HLG-240H-24AU	Mean Well Power Supply HLG 240W 24V IP67
	PWR-HLG-320H-24AU	Mean Well Power Supply HLG 320W 24V IP67

CABLE EXTENSIONS

	CBLEXT-STR-WR2.1-IP40-3M	3m Cable Extension for Strips Red, Black and White, 0.75mm ² wire
	CBLEXT-STR-WR2.1-IP40-5M	5m Cable Extension for Strips Red, Black and White, 0.75mm ² wire
	CBLEXT-STR-OC2.1-IP65-3M	3m Connector Extension for Strips 1x Red, 1x Black, 1x White, 0.75mm ² wires
	CBLEXT-STR-OC2.1-IP65-5M	5m Connector Extension for Strips 1x Red, 1x Black, 1x White, 0.75mm ² wires
	CBLEXT-STR-WR4.1-IP40-3M	3m Cable Extension for Strips 2x Red, 2x Black, 1x White, 0.75mm ² wires
	CBLEXT-STR-WR4.1-IP40-5M	5m Cable Extension for Strips 2x Red, 2x Black, 1x White, 0.75mm ² wires
	CBLEXT-STR-OC4.1-IP65-3M	3m Connector Extension for Strips 2x Red, 2x Black, 1x White, 0.75mm ² wires
	CBLEXT-STR-OC4.1-IP65-5M	5m Connector Extension for Strips 2x Red, 2x Black, 1x White, 0.75mm ² wires